



E55MJRL

ANY PLACE, ANY FUEL



| EVINRUDE MULTI FUEL ENGINE | E55MJRL |
|-----------------------------------|--|
| Shaft Length in (mm) / Color | 20" (508) / Tactical Black |
| Weight lbs (kg) | 270 (122.5) |
| Engine Type | Inline 2-cylinder Direct Injection Multi Fuel |
| Bore x Stroke in (mm) | 3.601 x 2.588 (91 x 66) |
| Displacement cu in (cc) | 52.7 (863) |
| Starting | Rope |
| Trim Method | Manual (Tilt Assist Cylinder and Trim Assist Strap) |
| Propshaft HP (kilowatts) | 55 HP (41 KW) @ 5500 RPM |
| Full Throttle Operating Range | 5500-6000 RPM |
| Gear Ratio | 2.67:1 |
| Fuel Induction | E-TEC™ Direct Fuel Injection with stratified low RPM combustion mode |
| Alternator | Variable Voltage Computer Controlled 75 Amp / 1100 Watt output with regulator |
| Cooling | Pressure and Temperature Controlled, Water Cooled |
| Steering | Tiller (Drop Down Handle) |
| Limited Warranty | 1 Year |
| Source Fuels | JP-4, JP-5, JP-8, Jet-A, Jet-B, Kerosene, Gasoline |

For more information visit brp.com

EVINRUDE®

